

Double Backer Speed Control

- Provides a reliable method to preset and resume the double facer speed
- Can be activated from remote stations
- Accurate rate is displayed



Features

Doublebacker run speed is set with thumbwheel switches on the front panel.

Three independent “slow down” speeds can be preset internally.

Command to speed up or slow down the doublebacker to these preset speeds can be initiated at the control panel or at optional remote stations.

The very accurate three digit rate meter displays machine speed in feet per minute or meters per minute.

Benefits

The ability to immediately increase to profitable running rates reduces production losses associated with increasing speed in multiple stages or steps.

Slow down speed presets permit the doublebacker to slow down for consistent splice and order change speeds.

Optional remote stations allow use by operators at several locations.

Accurate rate meter will assist operators and supervisors in setting and maintaining production goals.

General Specifications

Maximum Set Speed: 999 fpm (999 mpm).

Supply Voltage: 115v +/-10% 50/60 Hz. or 230v +/-10% 50/60 Hz.

Digit Size: .8” high (20mm).

Digit Color: Red

Mechanical Details

Maximum Cabinet Dimensions:
Height: 16” (406mm)
Width: 12” (305mm)
Depth: 7 1/2” (190mm)

Material: 14 gauge steel with speckle tone finish.

COPAR corporation

5744 West 77th Street Burbank, Illinois 60459
Telephone: (708) 496-1859 Fax: (708) 496-0079
www.copar.com